



ITEM NO.	SPEC. NO.	ITEM	Estimated Quantity	Unit of Measure
PART 1 - ASPHALT MILL & OVERLAY				
1	110	MOBILIZATION	1	LS
2	112	MAINTENANCE OF TRAFFIC	1	LS
3	302/SPL *	6" DGA FOR SUBGRADE REPAIR *	200	CY
4	402/403	VARIABLE THICKNESS ASPHALT PAVEMENT LEVELING (3/4" AT CURB TO 1-1/4" AT CENTER)	14,725	SY
5	402/403	1" ASPHALT PAVEMENT SURFACE WITH FIBER REINFORCEMENT	14,725	SY
6	408	ASPHALT MILLING (MILL TO CONCRETE SURFACE [2" AVG])	14,725	SY
7	SPL*	6" CONCRETE APRON/DRIVEWAY REPLACEMENT *	750	SF
8	SPL*	FULL DEPTH PAVEMENT REPAIR, ASPHALT, AS PER PLAN *	1,450	SY
9	SPL*	SPOT CURB REPAIR, AS PER PLAN *	750	LF
PART 2 - CONCRETE SPOT REPAIRS WITH JOINT & CRACK SEAL				
10	SPL*	FULL DEPTH PAVEMENT REPAIR, CONCRETE, AS PER PLAN *	100	SY
11	SPL	Joint and Crack Sealing for Portland Cement Concrete Streets (Remove sealant in existing joint or crack to 1/4" to 1/2" depth and fill with sealant such that the top of the sealant is flush with the top of pavement)	6,500	LF
PART 3 - STORM IMPROVEMENTS				
12	701	INSTALL STORM SEWER (12" DIAMETER)	80	LF
13	203/204	REMOVE EXSITING STORM INLET	5	EA
14	710	INSTALL STANDARD DOUBLE GRATE INLET	5	EA
15	710	INSTALL STANDARD 2x2 CATCH BASIN	1	EA
16	704	4" RIGID PERFORATED PVC PIPE UNDERDRAIN	20	LF
17	SPL	REPLACE VANE GRATE	4	EA