

[illegible]

STANDARD ODOT LOG W/ SULFATES (8.5 X 11) - OH DOT.GDT - 9/19/24 11:47 - X:\PROJECTS\240113501.GPJ

NOTES: NONE

ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; AUGER CUTTINGS MIXED WITH 1 BAG CEMENT

STANDARD ODOT LOG W/ SULFATES (8.5 X 11) - OH DOT GDT - 9/19/24 11:47 - X:\PROJECTS\240113501.GPJ

PROJECT: SR-84		DRILLING FIRM / OPERATOR: OHIO TESTBOR / CORE				DRILL RIG: CME 55 TRUCK				STATION / OFFSET:				EXPLORATION ID							
TYPE: BRIDGE		SAMPLING FIRM / LOGGER: OHIO TESTBOR / KKC				HAMMER: CME AUTOMATIC				ALIGNMENT:				B-002-0-23							
PID: N/A SFN: N/A		DRILLING METHOD: HSA / NQ				CALIBRATION DATE: 3/10/09				ELEVATION: 731.0 (NAVD88) EOB: 50.5 ft.				PAGE							
START: 5/2/24 END: 5/2/24		SAMPLING METHOD: SPT / NQ				ENERGY RATIO (%): 81.3				LAT / LONG: 41.623632, -81.415768				1 OF 2							
MATERIAL DESCRIPTION AND NOTES		ELEV.	DEPTHS		SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (G1)	SO4 ppm	BACK FILL
ASPHALT - 7 INCHES		731.0																			
CONCRETE - 8 INCHES		730.4	1																		
LOOSE TO MEDIUM DENSE, BROWN, GRAVEL AND STONE FRAGMENTS , LITTLE SAND, LITTLE SILT, TRACE CLAY, MOIST FILL		729.7	2		3	14	-	SS-1	-	-	-	-	-	-	-	-	9	A-1-a (V)	-		
			3		5																
			4		4	11	-	SS-2	-	70	11	6	12	1	NP	NP	NP	7	A-1-a (0)	-	
			5		4																
			6		5	14	-	SS-3	-	-	-	-	-	-	-	-	-	8	A-1-a (V)	-	
			7		5																
			8		4																
			9		3	8	-	SS-4	-	-	-	-	-	-	-	-	-	8	A-1-a (V)	-	
			10		3																
			11		4	15	-	SS-5	-	-	-	-	-	-	-	-	-	5	A-3 (V)	-	
MEDIUM DENSE, GRAY, FINE SAND , LITTLE GRAVEL, TRACE SILT, TRACE CLAY, MOIST		721.5	12		5																
LOOSE, GRAY, FINE SAND , LITTLE GRAVEL, TRACE SILT, TRACE CLAY, MOIST		719.5	13		6	14	-	SS-6	-	-	-	-	-	-	-	-	5	A-3 (V)	-		
			14		5																
			15		5	14	-	SS-7A	-	-	-	-	-	-	-	-	-	6	A-3 (V)	-	
			16		6																
@7.5': BROWN/GRAY		715.8	17		4																
VERY STIFF TO HARD, BROWN, SILTY CLAY , SOME SAND, LITTLE GRAVEL, MOIST		715.5	18		11	26	-	SS-7B	2.50	-	-	-	-	-	-	-	19	A-6b (V)	-		
VERY STIFF TO HARD, BROWN, SILT AND CLAY , SOME SAND, TRACE GRAVEL, MOIST		715.0	19		7			SS-8A	4.50	-	-	-	-	-	-	-	18	A-6a (V)	-		
		713.4	20		12			SS-8B	3.75	7	4	9	23	57	31	20	11	16	A-6a (8)	-	
VERY STIFF, GRAY, SILT AND CLAY , LITTLE SAND, TRACE GRAVEL, MOIST			21		14																
MEDIUM DENSE, BROWN, FINE SAND , TRACE SILT, TRACE CLAY, MOIST			22		4	18	-	SS-9	-	-	-	-	-	-	-	-	19	A-3 (V)	-		
			23		6																
			24		7																
			25		8	24	-	SS-10	-	-	-	-	-	-	-	-	-	20	A-3 (V)	-	
			26		10																
			27		11	22	-	SS-11	-	-	-	-	-	-	-	-	-	22	A-3 (V)	-	
			28		9																
			29		11																
@19.5': GRAY			30		5																
		705.5	31		10																
			32		12																
			33		15																
VERY STIFF TO HARD, GRAY, SANDY SILT , LITTLE		705.2	34					SS-13A	4.50	-	-	-	-	-	-	-	16	A-4a (V)	-		

